SAFETY DATA SHEET



Oxidizing Gas Mixture: Isoflurane / Nitrogen / Oxygen

Section 1. Identification

GHS product identifier	: Oxidizing Gas Mixture: Isoflurane / Nitrogen / Oxygen
Other means of identification	: Not available.
Product use	: Synthetic/Analytical chemistry.
SDS #	: 008200
Supplier's details	 Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road Suite 100 Radnor, PA 19087-5283 1-610-687-5253
24-hour telephone	: 1-866-734-3438

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: OXIDIZING GASES - Category 1 GASES UNDER PRESSURE - Compressed gas TOXIC TO REPRODUCTION (Fertility) - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 May cause or intensify fire; oxidizer. Contains gas under pressure; may explode if heated. Suspected of damaging fertility or the unborn child. May cause drowsiness and dizziness.
Precautionary statements	
General	: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Open valve slowly. Use only with equipment cleaned for Oxygen service.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from clothing, incompatible materials and combustible materials. Keep reduction valves, valves and fittings free from oil and grease. Use only outdoors or in a well-ventilated area. Avoid breathing gas.
Response	: In case of fire: Stop leak if safe to do so. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
Storage	: Store locked up. Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place.

Section 2. Hazards identification

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

Section 3. Composition/information on ingredients

: None known.

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

CAS number Product code	Not applicable.008200		
Ingredient name		%	CAS number
oxygen Nitrogen isoflurane		23.5 - 98 1 - 76.5 1 - 10	7782-44-7 7727-37-9 26675-46-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: As this product is a gas, refer to the inhalation section.
Most important symptoms	s/effects, acute and delayed
Potential acute health eff	
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Inhalation	 Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Frostbite	: Try to warm up the frozen tissues and seek medical attention.
Ingestion	: Can cause central nervous system (CNS) depression. As this product is a gas, refer to the inhalation section.
Over-exposure signs/syr	nptoms
Eye contact	: No specific data.
Date of issue/Date of revision	: 7/8/2017 Date of previous issue : No previous validation Version : 1 2/11

Section 4. First aid measures

: Adverse symptoms may include the following:, nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths, skeletal malformations
 Adverse symptoms may include the following:, reduced fetal weight, increase in fetal deaths, skeletal malformations
 Adverse symptoms may include the following:, reduced fetal weight, increase in fetal deaths, skeletal malformations
dical attention and special treatment needed, if necessary
 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
: No specific treatment.
: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Fire-fighting measures

-	_
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Contains gas under pressure. Oxidizing material. This material increases the risk of fire and may aid combustion. Contact with combustible material may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst or explode.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protecti	ve equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions	:	Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	onta	ainment and cleaning up
Small spill	:	Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.
Large spill	:	Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact

information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep away from clothing, incompatible materials and combustible materials. Keep reduction valves free from grease and oil. Empty containers retain product residue an can be hazardous. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.	d
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.	e
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Separate from acids, alkalies, reducing agents and combustibles. Keep container tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder	

Section 8. Exposure controls/personal protection

Control parameters Occupational exposure limits oxygen None. Nitrogen Oxygen Depletion [Asphyxiant] isoflurane None. **Appropriate engineering** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or controls other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. : Emissions from ventilation or work process equipment should be checked to ensure **Environmental exposure** they comply with the requirements of environmental protection legislation. In some controls cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

temperatures should not exceed 52 °C (125 °F).

Individual protection measures

Section 8. Exposure controls/personal protection

-	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	Gas.	
Color	Not available.	
Melting/freezing point	-210.01°C (-346°F) This is based on data for the following ingredient: nitrogen. Weighted average: -214.72°C (-354.5°F)	
Critical temperature	Lowest known value: -146.95°C (-232.5°F) (nitrogen).	
Odor	Not available.	
Odor threshold	Not available.	
рН	Not available.	
Flash point	Not available.	
Burning time	Not applicable.	
Burning rate	Not applicable.	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Lower and upper explosive (flammable) limits	Not available.	
Vapor pressure	Not available.	
Vapor density	Highest known value: 1.1 (Air = 1) (oxygen). Weighted average: 1.04 (Air = 1)	
Gas Density (lb/ft ³)	Weighted average: 0.08	
Relative density	Not applicable.	
Solubility	Not available.	
Solubility in water	Not available.	
Partition coefficient: n- octanol/water	Not available.	

Date of issue/Date of revision

5/11

Section 9. Physical and chemical properties

Auto-ignition temperature	1	Not available.
Decomposition temperature	:	Not available.
SADT	1	Not available.
Viscosity	:	Not applicable.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Hazardous reactions or instability may occur under certain conditions of storage or use. Conditions may include the following: contact with combustible materials Reactions may include the following: risk of causing fire
Conditions to avoid	: No specific data.
Incompatible materials	: Highly reactive or incompatible with the following materials: combustible materials reducing materials grease oil
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
isoflurane	LC50 Inhalation Gas. LC50 Inhalation Vapor		26499 ppm 58.5 g/m³	1 hours 4 hours

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
isoflurane	-	3	-

Reproductive toxicity

Not available.

Section 11. Toxicological information

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
isoflurane	Category 3	Not applicable.	Narcotic effects

<u>Specific target organ toxicity (repeated exposure)</u>

Not available.

Aspiration hazard

Not available.

: Not available. Information on the likely routes of exposure

routes of exposure	
Potential acute health effects	
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Ingestion	: Can cause central nervous system (CNS) depression. As this product is a gas, refer to the inhalation section.

Symptoms related to the physical, chemical and toxicological characteristics Eye contact : No specific data. Inhalation : Adverse symptoms may include the following:, nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths, skeletal malformations : Adverse symptoms may include the following:, reduced fetal weight, increase in fetal Skin contact deaths, skeletal malformations Ingestion : Adverse symptoms may include the following:, reduced fetal weight, increase in fetal deaths, skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: Suspected of damaging the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

Section 11. Toxicological information

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Inhalation (gases)	114608.2 ppm

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
oxygen	0.65	-	low
Nitrogen	0.67	-	low
isoflurane	2.06	-	low

Mobility in soil

Soil/water partition	: Not
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

available.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty Airgas-owned pressure vessels should be returned to Airgas. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate
	containers of inters may retain some product residues. Do not puncture of incinerate

Section 14. Transport information

DOT	TDG	Mexico	IMDG	ΙΑΤΑ
UN3156	UN3156	UN3156	UN3156	UN3156
COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen)	COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen)	COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen)	COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen)	COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen)
2.2 (5.1)	2.2 (5.1)	2.2 (5.1)	2.2 (5.1)	2.2 (5.1)
-	-	-	-	-
No.	No.	No.	No.	No.
	UN3156 COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) 2.2 (5.1) 2.2 (5.1)	UN3156 UN3156 COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) 2.2 (5.1) 2.2 (5.1) Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system Image: Comparison of the system </td <td>UN3156 UN3156 UN3156 COMPRESSED GAS, (XIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, (XIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, (OXIDIZING, N.O.S. (oxygen, nitrogen) 2.2 (5.1) 2.2 (5.1) 2.2 (5.1) Image: Complex of the second sec</td> <td>UN3156 UN3156 UN3156 UN3156 COMPRESSED GAS, (XIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) 2.2 (5.1) 2.2 (5.1) 2.2 (5.1) 2.2 (5.1) Image: Complexity of the second secon</td>	UN3156 UN3156 UN3156 COMPRESSED GAS, (XIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, (XIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, (OXIDIZING, N.O.S. (oxygen, nitrogen) 2.2 (5.1) 2.2 (5.1) 2.2 (5.1) Image: Complex of the second sec	UN3156 UN3156 UN3156 UN3156 COMPRESSED GAS, (XIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) COMPRESSED GAS, OXIDIZING, N.O.S. (oxygen, nitrogen) 2.2 (5.1) 2.2 (5.1) 2.2 (5.1) 2.2 (5.1) Image: Complexity of the second secon

Section 14. Transport information

Additional -	Product cla		-	-	
information	per the follo sections of				
	Transportal				
	Dangerous				
		s: 2.13-2.17			
	(Class 2), 2 (Class 5).	2.23-2.25			
	(Class 5).				
	Explosive				
	Limited Qu	lantity Index			
	0				
	ERAP Inde	x			
	3000	-			
	Desserver				
	Passenger Ship Index				
	Forbidden				
	Passenger				
	Road or Ra 75	all Index			

"Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according	: Not available.
to Annex II of MARPOL	
73/78 and the IBC Code	

Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a	a) CDR Exempt/Partial ex	emption: Not determined		
-	United S	tates inventory (TSCA 8b	: Not determined.		
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed	I			
Clean Air Act Section 602 Class I Substances	: Not listed	I			
Clean Air Act Section 602 Class II Substances	: Not listed	I			
DEA List I Chemicals (Precursor Chemicals)	: Not listed	I			
DEA List II Chemicals (Essential Chemicals)	: Not listed	I			
SARA 302/304					
Composition/information	<u>on ingredien</u>	<u>ts</u>			
No products were found.					
SARA 304 RQ SARA 311/312	: Not appli	cable.			
Classification	: Refer to S	Section 2: Hazards Identific	cation of this SDS for clas	sification of substance	ə.
State regulations					
Massachusetts	: The follow (LIQUIFII	wing components are listed ED)	: OXYGEN (LIQUID); NIT	ROGEN; NITROGEN	
Date of issue/Date of revision	: 7/8/2017	Date of previous issue	: No previous validation	Version : 1	9/11


Section 15. Regulatory information

New York	: None of the components are listed.
New Jersey	: The following components are listed: OXYGEN; NITROGEN
Pennsylvania	: The following components are listed: OXYGEN; NITROGEN
International regulations	
International lists	
National inventory	
Australia	: Not determined.
Canada	: Not determined.
China	: Not determined.
Europe	: All components are listed or exempted.
Japan	: Not determined.
Malaysia	: Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: All components are listed or exempted.
<u>Canada</u>	
WHMIS (Canada)	: Class A: Compressed gas. Class C: Oxidizing material.
	CEPA Toxic substances: None of the components are listed. Canadian ARET: None of the components are listed. Canadian NPRI: None of the components are listed.
	Alberta Designated Substances: None of the components are listed. Ontario Designated Substances: None of the components are listed. Quebec Designated Substances: None of the components are listed.

Section 16. Other information

Canada Label requirements	: Class A: Compressed gas.
	Class C: Oxidizing material.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
Ox. Gas 1, H270	On basis of test data
Press. Gas Comp. Gas, H280	On basis of test data
Repr. 2, H361 (Fertility)	Calculation method
Repr. 2, H361 (Unborn child)	Calculation method
STOT SE 3, H336	Expert judgment
History	· · · ·

<u>Inotory</u>	
Date of printing	: 7/8/2017
Date of issue/Date of revision	: 7/8/2017
Date of previous issue	: No previous validation
Version	: 1
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	: Not available.

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.