SAFETY DATA SHEET



Nonflammable Gas Mixture: Carbon Monoxide / Nitric Oxide / Nitrogen / Sulfur Dioxide

Section 1. Identification

GHS product identifier	: Nonflammable Gas Mixture: Carbon Monoxide / Nitric Oxide / Nitrogen / Sulfur Dioxide
Other means of identification	: Not available.
Product type	: Gas.
Product use	: Synthetic/Analytical chemistry.
SDS #	: 012833
Supplier's details	: Airgas USA, LLC and its affiliates 259 North Radnor-Chester Road Suite 100 Radnor, PA 19087-5283 1-610-687-5253
24-hour telephone	: 1-866-734-3438

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: GASES UNDER PRESSURE - Compressed gas EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 Contains gas under pressure; may explode if heated. Causes serious eye irritation. May damage fertility or the unborn child. May displace oxygen and cause rapid suffocation.
Precautionary statements	
General	: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction.
Prevention	: Obtain special instructions before use. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up. Protect from sunlight. Store in a well-ventilated place.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: In addition to any other important health or physical hazards, this product may displace oxygen and cause rapid suffocation.

1/12

Section 3. Composition/information on ingredients

Substance/mixture : Mixture Other means of : Not available. identification **Product code** : 012833

% Ingredient name **CAS** number Nitrogen 98.19 - 99.898 7727-37-9 carbon monoxide 0.1 - 0.9999 630-08-0 sulphur dioxide 7446-09-5 0.00001 - 0.6 Nitric Oxide 0.00001 - 0.21 10102-43-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: As this product is a gas, refer to the inhalation section.

Most important sym	ptoms/effects, acute	and delayed

Potential acute health effects Eye contact : Causes serious eye irritation. Contact with rapidly expanding gas may cause burns or frostbite. Inhalation : No known significant effects or critical hazards. **Skin contact** : Contact with rapidly expanding gas may cause burns or frostbite. **Frostbite** : Try to warm up the frozen tissues and seek medical attention. Ingestion : As this product is a gas, refer to the inhalation section. **Over-exposure signs/symptoms** Eye contact : Adverse symptoms may include the following:, pain or irritation, watering, redness : Adverse symptoms may include the following:, reduced fetal weight, increase in fetal Inhalation deaths, skeletal malformations Skin contact : Adverse symptoms may include the following:, reduced fetal weight, increase in fetal deaths, skeletal malformations : Adverse symptoms may include the following:, reduced fetal weight, increase in fetal Ingestion deaths, skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Date of issue/Date of revision	: 2/3/2021	Date of previous issue	: 5/24/2019	Version : 1.01	2/12
--------------------------------	------------	------------------------	-------------	----------------	------

Section 4. First aid measures

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

	-
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: nitrogen oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures		
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
Environmental precautions	:	Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for containment and cleaning up				
Small spill	:	Immediately contact emergency personnel. Stop leak if without risk.		
Large spill	;	Immediately contact emergency personnel. Stop leak if without risk. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.		

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Do not get in eyes or on skin or clothing. Avoid breathing gas. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement. Empty containers retain product residue and can be hazardous. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid exposure during pregnancy.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F). Store locked up. Keep container tightly closed and sealed until ready for use. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits
Nitrogen			ACGIH TLV (United States, 3/2019). Oxygen Depletion [Asphyxiant].
carbon monoxide			California PEL for Chemical Contaminants (<i>Table AC-1</i>) (United States). PEL: 25 ppm 8 hours. CEIL: 200 ppm ACGIH TLV (United States, 3/2019). TWA: 25 ppm 8 hours. TWA: 29 mg/m ³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 35 ppm 8 hours. TWA: 40 mg/m ³ 8 hours. CEIL: 200 ppm CEIL: 229 mg/m ³ NIOSH REL (United States, 10/2016). TWA: 35 ppm 10 hours. TWA: 40 mg/m ³ 10 hours. CEIL: 200 ppm CEIL: 229 mg/m ³ OSHA PEL (United States, 5/2018).
			TWA: 50 ppm 8 hours. TWA: 55 mg/m ³ 8 hours.
sulphur dioxide			California PEL for Chemical Contaminants (<i>Table AC-1</i>) (United States). PEL: 2 ppm 8 hours. STEL: 5 ppm 15 minutes. ACGIH TLV (United States, 3/2019). STEL: 0.25 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 2 ppm 8 hours.
ate of issue/Date of revision	: 2/3/2021	Date of previous issue	:5/24/2019 Version :1.01 4/12

Section 8. Exposure controls/personal protection

Section 8. Expos	are controls/personal protection
Nitric Oxide	TWA: 5 mg/m³ 8 hours. STEL: 5 ppm 15 minutes. STEL: 10 mg/m³ 15 minutes. NIOSH REL (United States, 10/2016). TWA: 2 ppm 10 hours. TWA: 5 mg/m³ 10 hours. STEL: 5 ppm 15 minutes. STEL: 13 mg/m³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 5 ppm 8 hours. ACGIH TLV (United States, 3/2019). TWA: 13 mg/m³ 8 hours. MCGIH TLV (United States, 3/2019). TWA: 25 ppm 8 hours. TWA: 31 mg/m³ 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 30 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 25 ppm 10 hours. TWA: 30 mg/m³ 10 hours. TWA: 30 mg/m³ 10 hours. TWA: 30 mg/m³ 10 hours. TWA: 30 mg/m³ 8 hours. MCSHA PEL (United States, 5/2018). TWA: 25 ppm 8 hours. TWA: 30 mg/m³ 8 hours.
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measured	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

```
Respiratory protection
```

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	1	Gas.
Color	1	Not available.
Odor	1	Not available.
Odor threshold	:	Not available.
рН	1	Not available.
Melting point	:	-210.01°C (-346°F) This is based on data for the following ingredient: nitrogen.
Boiling point	:	Not available.
Critical temperature	:	Lowest known value: -146.95°C (-232.5°F) (nitrogen).
Flash point	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	1	Not available.
(flammable) limits		
Vapor pressure		Not available.
Vapor density		Highest known value: 0.97 (Air = 1) (nitrogen).
Gas Density (lb/ft ³)	1	Only known value: 0.072 (nitrogen).
Relative density	1	Not applicable.
Solubility	1	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	1	Not available.
octanol/water		
Auto-ignition temperature		Not available.
Decomposition temperature		Not available.
Viscosity	1	Not applicable.
Flow time (ISO 2431)	:	Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Hazardous polymerization	: Under i	normal conditions of storage an	nd use, hazardo	ous polymerization w	vill not	occur.
Date of issue/Date of revision	: 2/3/2021	Date of previous issue	: 5/24/2019	Version	: 1.01	6/12

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
sulphur dioxide	LC50 Inhalation Gas. LC50 Inhalation Gas. LC50 Inhalation Gas.	Rat	3760 ppm 2520 ppm 115 ppm	1 hours 1 hours 1 hours

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
sulphur dioxide	Eyes - Mild irritant	Rabbit	-	768 hours 6	-
				ppm	

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
sulphur dioxide	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
carbon monoxide	Category 1	-	-

Aspiration hazard

Not available.

Information on the likely : Not available.

Potential acute health effects		
Eye contact	:	Causes serious eye irritation. Contact with rapidly expanding gas may cause burns or frostbite.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Contact with rapidly expanding gas may cause burns or frostbite.
Ingestion	:	As this product is a gas, refer to the inhalation section.

Symptoms related to	symptoms related to the physical, chemical and toxicological characteristics						
Eye contact	: Adverse symptoms may include the following:, pain or irritation, watering, redness						
Inhalation	: Adverse symptoms may include the following:, reduced fetal weight, increase in fetal deaths, skeletal malformations						

Section 11. Toxicological information

		0
Skin contact	:	Adverse symptoms may include the following:, reduced fetal weight, increase in fetal deaths, skeletal malformations
Ingestion	:	Adverse symptoms may include the following:, reduced fetal weight, increase in fetal deaths, skeletal malformations
Delayed and immediate effect	<u>cts</u>	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	1	Not available.
<u>Long term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ect	<u>s</u>
Not available.		
General	:	No known significant effects or critical hazards.
Carcinogenicity	1	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	May damage the unborn child.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	May damage fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Nitrogen	0.67	-	low

Mobility in soil

Soil/water partition	: Not
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty Airgas-owned pressure vessels should be returned to Airgas. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT	TDC	Maxiaa		
	DOT	TDG	Mexico	IMDG	IATA
UN number	UN1956	UN1956	UN1956	UN1956	UN1956
UN proper shipping name	COMPRESSED GAS, N.O.S. (nitrogen, carbon monoxide)				
Transport hazard class(es)	2.2	2.2	2.2	2.2	2.2
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

"Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Additional information

TDG Classification	:	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). Explosive Limit and Limited Quantity Index 0.125 Passenger Carrying Road or Rail Index 75
Special precautions for user	:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	:	Not available.

Section 15. Regulatory information

U.S. Federal regulations	1	TSCA 8(a) CDR Exempt/Partial exemption: Not determined
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	:	Not listed
Clean Air Act Section 602 Class I Substances	:	Not listed

9/12

Section 15. Regulatory information

Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed

SARA 302/304

Composition/information on ingredients

				SARA 3	02 TPQ	SAF	RA 304 RQ
Name		%	EHS	(lbs)	(gallons)	(lbs) (gallons)
sulphur dioxide Nitric Oxide		0.00001 - 0.6 0.00001 - 0.21	Yes. Yes.	500 100	-	500 10	
SARA 304 RQ	: 9523.4 lb	s / 4323.6 kg					
<u>SARA 311/312</u>							
Classification	: Refer to Section 2: Hazards Identification of this SDS for classification of substance.						
tate regulations							
Massachusetts	: The follow	wing components	are listed	: NITRO	GEN; NITROGE	N (LIC	QUIFIED)
New York	: None of the components are listed.						
New Jersey	: The follow	wing components	are listed	: NITRO	GEN		
Pennsylvania	: The follow	wing components	are listed	: NITRO	GEN		
<u>California Prop. 65</u>							
▲ WARNING: This p known to the State P65Warnings.ca.s	e of California to ca						lioxide, which are ormation go to www
Ingredient name					No significant l	risk	Maximum acceptable dosag level

Carbon monoxide sulfur dioxide

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Europe	: All components are listed or exempted.


Yes.

Section 15. Regulatory information

0	-
Japan	: Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: All components are active or exempted.
Viet Nam	: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification		Justification
GASES UNDER PRESSUR EYE IRRITATION - Categor TOXIC TO REPRODUCTIO	y 2A	On basis of test data Expert judgment Calculation method
History		
Date of printing	: 2/3/2021	
Date of issue/Date of revision	: 2/3/2021	
Date of previous issue	: 5/24/2019	
Version	: 1.01	

: 2/3/2021

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	: Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.